

TRIAC S ECONOMY



The most commonly used built-in device for pellet and woodchip heating systems.

- Built-in device for fast and safe ignition
- Operational safety thanks to electronic protection of the heating element
- Blower and heating element can be controlled separately
- Fulfils Flicker Standards and RoHS Directives



SPECIFICATIONS



230 V 1000 W

Voltage	V~	230
Power consumption	W	1000
Frequency	Hz	50 / 60
Temperature	°C	250
Air flow (20°C)	l/min	230
Pressure static	Pa	ca. 3000 (30 mbar)
Noise emission level LpA	dB	65
Weight	kg	1.3
Connection lead		Silicon, 3 x 1 mm ² x 2 m
Marking of conformity		
Protection class II		


230 V 1600 W

Voltage	V~	230
Power consumption	W	1600
Frequency	Hz	50 / 60
Temperature	°C	600

Process Heat > Ignition blower > TRIAC S ECONOMY

Air flow (20°C)	l/min	230
Pressure static	Pa	ca. 3000 (30 mbar)
Noise emission level LpA	dB	65
Weight	kg	1.3
Connection lead		Silicon, 3 x 1 mm ² x 2 m
Marking of conformity		
Protection class II		

ACCESSORIES



Air hose \varnothing 38 mm

107.286 - PVC air hose \varnothing 38 mm



Hose clip, \varnothing 38 mm and
 \varnothing 60 mm

107.287 - Hose clip for \varnothing 38 mm and
 \varnothing 60 mm air hose